FYRECHOKE



MICRO FIRE COLLARS



Fyrechoke Micro Fire Collars are a compact sized retrofit product, designed to provide maximum protection against the spread of fire & smoke through walls, floors and ceilings where they are penetrated by plastic conduits.

Fyrechoke Micro Fire Collars are simple to install, using an integrated 'slide lock joint' mechanism, the two halves of the collar simply fit around the pipe and slide together. The collar is then fastened to the wall, floor or ceiling using integrated fixing lugs at the base of the collar.

Trafalgar's Fyrechoke fire collar range have been extensively tested to AS1530.4 and AS4072.1 in accordance with the Building Code of Australia. They have been installed on building sites throughout Australia and the world.

Thanks to the innovative two piece 'slide lock joint' mechanism, Fyrechoke two piece collars are ideal for use in tight, difficult to reach locations. Their stainless steel casing is supplied standard and is ideal for use in aggressive environments.

APPLICATION

Trafalgar Fyrechoke Micro Fire Collars are designed and tested for use in wall, floor and ceiling applications. They are fixed using screws or dynabolts depending on the fire barrier type.

Fyrechoke Conduit Micro Fire Collars are suitable for all types of conduits including electrical, data or mechanical services. They are suitable for flexible and rigid plastic conduits.



KEY FEATURES AND BENEFITS

- Known and trusted brand
 Benchmark Quality
- Easily retrofit with integrated slide fastening
- Cost effective— manufactured from recycled stainless steel
- Fully tested to AS1530.4 & AS4072.1
- Up to -/240/240 (barrier dependent)
- Corrosion resistant stainless steel casing
- Walls, floors & ceilings
- For further information on these products, contact Trafalgar

The information contained in this brochure was correct at the time of printing. E&OE



Our Products are available Nationwide Sales: 1800 888 714

Trafalgar is the well respected brand, synonymous with the supply of engineered solutions for the containment of fire, smoke and sound. As the foremost Australian owned supplier of passive fire protection systems, Trafalgar's products have been specified and installed into Australian buildings for over 60 years.



FYRECHOKE CONDUIT MICRO FIRE COLLARS					
Nominal Collar Size (mm)	Conduit Outside Diameter (mm)	D1	D2	H1	D2 D1
25	25	27	36	50	
32	32	40	50	50	H1
40	40	45	55	50	

PRODUCT DESCRIPTION

COLOUR / APPEARANCE - Stainless steel casing.

INSTALLATION - Easily retro fit, the two halves of the collar slide together, securing the collar around the conduit. Two integrated screw fixing tabs are then used to fix the collar to the wall, floor or ceiling.


DURABILITY - Made from a highly durable and corrosion resistant stainless steel for maximum quality & durability.

MAINTENANCE - Fyrechoke collars require no maintenance.

TESTING - Fyrechoke Micro Fire Collars are fire tested to AS 1530.4 & AS 4072.1 and fully comply with the Building Code of Australia.

ALSO AVAILABLE - Trafalgar offers a full range of fire collars and fire stopping products, along with a complete range of access panels.





SPECIFICATION

All plastic conduit penetrations are to be sealed, so as to maintain the fire rating of the element (wall, floor or ceiling) in accordance with AS1530.4 using Trafalgar Fyrechoke Conduit Micro Fire Collars as detailed in Trafalgar's printed installation instructions.

Trafalgar reserves the right to change specifications without notice. Please check with your supplier at the time of order.

