



Technical Data Sheet

Bostik Ultragrip

Plasterboard Stud Adhesive

DESCRIPTION

Bostik Ultragrip is a specially formulated non-toxic high strength acrylic stud adhesive designed to minimize nail and screw “popping” caused by timber shrinkage or frame movement if applied in accordance with AS 2589-1983. **Bostik Ultragrip** reduces the quantities of nails and screws required to fix plasterboard, therefore reducing the fastener head stopping and finishing requirements.

FEATURES

- ✓ H2 LOSP Formulated
- ✓ Suitable for timber and metal frames
- ✓ High bond strength
- ✓ Water-based non-toxic
- ✓ Non slump
- ✓ Suitable for vertical, horizontal
- ✓ Overhead applications
- ✓ Conforms to AS 2753-1985.

RECOMMENDED USES

- ✓ To fix plasterboard to steel or timber studs and frames (in conjunction with nails and screws)
- ✓ Filling irregular gaps between plasterboard and frame
- ✓ Bonding timber floors to timber
- ✓ Bonding timber to concrete or metal
- ✓ Bonding chipboard, plywood, masonite and Hardie-Flex sheeting to joints or solid floors/walls

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

All surfaces must be clean, free from dirt, dust and laitance and loose material. All surfaces to be treated must be structurally sound and all previous coatings and adhesions removed prior to application of **Bostik Ultragrip**. All surfaces must be dry and free from moisture. **Bostik Ultragrip Stud Adhesive** must be used in conjunction with nails or screws and is not single plasterboard sheet fixing system. To dispose **Bostik Ultragrip** sausage, simply hold sausage upright and cut the top off the foil below the metal clip. Place sausage into 37cm barrel gun then screw on end cap with nozzle. With controlled gun trigger pressure, apply **Bostik Ultragrip** to wall studs and ceiling joists or battens in daubs 15mm to 25mm high.

APPLICATION

Apply **Bostik Ultragrip** to walls in controlled daubs at 120mm centres and a minimum of 200mm from fixing points from the edge of the board. Ensure full contact between the sheets and **Bostik Ultragrip** until adhesives sets. Ceiling daubs should be 200mm and 400mm from recessed edge. DO NOT nail or screw through **Bostik Ultragrip**. Walls should be nailed at 150mm centres, opening at 300mm centres. Ceilings should be double nailed at centre line of ceiling joists 60mm apart. Nail edge sheets at butt joints, around openings and ceiling joist at 150mm centres. Or nail or screw the wall and ceiling sheets in accordance with board manufacturers' instructions. **Bostik Ultragrip** will dry and gain full strength in 24 hours. No mixing is required, simply use directly from sausage or pail.



COVERAGE

1 litre will cover 1 square metre at 1mm thickness

IMPORTANT NOTES

- Do not freeze or store below 5°C
- Do not use moist or wet timber
- Do not apply to pre-painted surfaces
- Not suitable as a tile adhesive
- Internal use only
- Do not apply on unseasoned or green timber
- Use in conjunction with screws or nails to fix plasterboard.

Bostik Co-Operative Test Program

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

PERFORMANCE PROPERTIES

Colour/s	Pink
Appearance	Non sag paste
Specific gravity	1.46 ± 0.02
Application Temperature	5°C to 35°C

Cure system	Water based
Full cure time	24 hours (min. @ 25°C)
Flammability	Non flammable
Tack free time	15 minutes

STORAGE & SHELF LIFE

Store between 5°C and 27°C. DO NOT FREEZE Shelf life is 12 months in original unopened container replace lid tightly when not in use.

SAFETY PRECAUTIONS

SEE THE MATERIAL SAFETY DATA SHEET FOR ADDITIONAL INFORMATION.

EMERGENCY INFORMATION: 1800 033 111 (ALL HOURS)

MSDS can be downloaded from www.bostik.com.au

voccertificates.australia@bostik.com

PACKAGING

Bostik Ultragrip is available in 850gm sausages and 5.2kg pails.

CLEAN-UP

Clean up with water before adhesive cures

PRODUCT DETAILS

ITEM NO	ITEM NAME	SIZE	COLOUR
258873	ULTRAGRIP	5.2 KG	PINK
248452	ULTRAGRIP	850 GM – 600ML	PINK



The information in this Technical Data Sheet is intended for the assistance of purchasers and is of a general nature. It reflects the extent of our knowledge and experience of our products and is based on tests which we believe to be reliable. However, no guarantee of accuracy can be given due to the wide range of surfaces, environmental and field conditions and variations encountered in raw materials, manufacturing equipment and methods at the place where the work is performed. Some of these will be beyond our knowledge or control. We recommend purchasers carry out their own tests to determine the suitability of the product for their particular purposes. Bostik Australia Pty Ltd limits its liability to replacement of the products or refund of the purchase price, but this limitation does not affect consumers' rights which cannot by law be excluded.

**ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF
BOSTIK AUSTRALIA PTY LTD**

Head Office

Bostik Australia Pty Ltd, 51-71 High Street, Thomastown Vic 3074

A.B.N. 79 003 893 838

Phone: (03) 9279 9333

Fax: (03) 9261 4744

Phone Construction/ASA:

Toll free 1300 364 710

Product Enquires:

construction.australia@bostik.com



Quality endorsed ISO9001 (Thomastown site)
TS16949 (Automotive)

Product: Ultragrip
Issue Date: July 2007
Issue No. 2
Author: AC
Division :Construction
Total Pages: 3